

RDW

#### **THE NETHERLANDS** (N E D E R L A N D)





### COMMUNICATION

Concerning<sup>(1)</sup>:

- approval granted

- approval extended
- approval refused
- approval withdrawn
- production definitely discontinued

of a type of mechanical coupling device or component pursuant to Regulation number 55.

#### Approval number: E4-55R-010917

**Extension number: 00** 

Approva	l mark:	See example of type plate.
1.	Trade name or mark of the device or component	: Monoflex
2.	Manufacturer's name for the type of device or component	: 307495600001
3.	Manufacturer's name and address	: Monoflex Nordic AB Nibblegatan 21, Box 14 734 21 Hallstahammar Sweden
4.	If applicable, name and address of the manufacturer's representative	: Not applicable
5.	Alternative supplier's name or trade marks applied to the device or component	:
6.	Name and address of company or body taking responsibility for the conformity of production	: See section 3.
7.	Submitted for approval on	: 24-09-2016



P.O. Box 777 2700 AT Zoetermeer The Netherlands Vehicle Admission & Surveillance

#### Approval number: E4-55R-010917

- 8. Technical service responsible for conducting approval tests
  8. Technical service responsible for conducting approval tests
  9. Box 777
  2700 AT Zoetermeer, The Netherlands.
- 9. Brief description
- 9.1. Type and class of device or component : Coupling ball and towing bracket, A50-X

:

:

- 9.2. Characteristic values
- 9.2.1. Primary values:

D	U	D <sub>c</sub>	V	S
(kN)	(tonnes)	(kN)	(kN)	(kg)
11,60	-	-	-	90

Alternative values:

1 memative varaet	,			
D	U	D <sub>c</sub>	V	S
(kN)	(tonnes)	(kN)	(kN)	(kg)
-	-	-	-	-

9.3. For class A mechanical coupling devices or components, including towing brackets:

Vehicle manufacturer's maximum permissible vehicle mass	:	2555 kg
Distribution of maximum permissible vehicle mass between the axles	:	Front axle 1370 kg, Rear axle 1235 kg
Vehicle manufacturer's maximum permissible towable trailer mass	:	2200 kg
Vehicle manufacturer's maximum permissible static mass on coupling ball	:	90 kg
Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver	:	2055 kg
Loading condition under which the tow ball height of a mechanical coupling device fitted to category M1 vehicles is to be measured – see paragraph 2 of annex 7, appendix 1	:	Mass according to Annex 7 - Appendix 1, section 2.1
For class B coupling heads, is the coupling head intended to be fitted to an unbraked trailer	:	<del>Yes / no</del> / not applicable <sup>(1)</sup>

9.4.

**RDW** 

# Approval number: E4-55R-010917

10.	Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points given by the vehicle manufacturer	: See documentation.
11.	Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component	: See fitting instructions.
12.	Additional information where the use of the coupling device or component is restricted to special types of vehicles – see annex 5, paragraph 3.4.:	: See fitting instructions.
13.	For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type	: Not applicable
14.	Date of test report	: 10-02-2017
15.	Number of test report	: RDW-55R-0048573
16.	Approval mark position	: On type plate
17.	Reason(s) for extension of approval	: Not applicable
18.	Approval	: granted/extended/refused/withdrawn <sup>(1)</sup>
19.	Place	: Zoetermeer
20.	Date	: 10-02-2017
21.	Signature	

X. vàn den Berg

## Approval number: E4-55R-010917

22. The list of documents deposited with the Administration Service which has granted the approval:

•	Instructions for fitting and/or use	: 41 page(s)
٠	Technical drawings of the coupling device	: 11 page(s)
•	Example of type plate.	: 1 page(s)
٠	Fixing points drawing made by the vehicle manufacturer	: <u>1 page(s)</u> +

Total : 54 page(s)

Remark(s):



<sup>&</sup>lt;sup>(1)</sup> Strike out what does not apply.