

Reason for extension:

ECE TYPE-APPROVAL CERTIFICATE

Communication concerning the approval granted of a type of mechanical coupling device or component pursuant to Regulation No.55.



N/A

Approval No: <u>E24 55R-010346</u> Extension No: *N/A*

| Reason for extension. | | IVA |
|-----------------------|---|--|
| 1. | Trade name or mark of the device or component: | SIARR – Westfalia - Monoflex |
| 2. | Manufacturer's name for the type of device or component: | SI216 Non-standard coupling ball 50 |
| 3. | Manufacturer's name and address: | S.I.A.R.R. Sas, Rue du General de Gaulle, F-76810 Luneray. |
| 4. | If applicable, name and address of the manufacturers representative: | N/A |
| 5. | Alternative supplier's names or trade marks applied to the device or component: | N/A |
| 6. | Name and address of the company or body taking responsibility for the conformity of production: | See 3. above |
| 7. | Submitted for approval on: | Week 04, 2013(dynamic) 14.06.2010 / 05.10.2010 (static) |
| 8. | Technical service responsible for conducting approval tests: | TÜV SÜD Auto Service GmbH, Westendstraße 199, D-80686 München, Germany. |
| 9. | Brief description | |
| 9.1 | Type and class of device or component: | Type: SI216 Class: A50-X |



Approval No: <u>E24 55R-010346</u> Extension No: *N/A*

| 0.0 | ~1 | | | |
|-----|---------|---------|-------|-----|
| 9.2 | Charact | eristic | value | èS. |

9.2.1 Primary values:

D: 8,62 kN

Dc: -S: 75 kg

U: -V: --

Alternative values:

D: -Dc: -S: -U: -V: --

9.3 For Class A mechanical coupling devices or components, including towing brackets:

Vehicle manufacturer's maximum permissible vehicle mass: 1950 kg

Distribution of maximum permissible vehicle mass between the axles:

Vehicle manufacturer's maximum permissible towable trailer mass:

Vehicle manufacturer's maximum permissible static mass on coupling ball:

Maximum mass of vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied)but not including driver:

Loading condition under which the tow ball height of a mechanical coupling device fitted to category M1 vehicles is to be measured – see paragraph 2 of annex 7, appendix 1:

9.4 For class B coupling heads, is the coupling head intended to be fitted to an unbraked O1 trailer: (yes/no)

10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points given by the manufacturer

11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component:

Jo kg

Front: 800-1050kg, Back: 750-950kg

1600 kg

75 kg

1500kg

Dimensions given by the vehicle manufacturer.

N/A

See manufacturer's documentation.

See manufacturer's documentation.



Approval No: **E24** 55R-010346 Extension No: N/A

| 12. | Additional information where the use of coupling device or | | |
|-----|--|--|--|
| | component is restricted to special types of vehicles | | |
| | - see annex 5 naragraph 3.4. | | |

see annex 5, paragraph 3.4:

See manufacturer's documentation.

13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type:

N/A

14. Date of test report: 06.02.2014

15. Number of test report: 14-00071-CX-GBM-00

16. Approval mark position: Manufacturer's plate on socket plate,

riveted.

17. Reason(s) for extension of approval: N/A

18. Approval granted/extended/refused/withdrawn: Granted

19: Place: Dublin

20. Date: 26th May, 2014.

21. Signature:



22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.